

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-312646

(43)Date of publication of application : 09.11.1999

(51)Int.Cl.

H01L 21/205  
C23C 16/50  
C23F 4/00  
H01L 21/3065  
// H05H 1/46

(21)Application number : 10-119022

(71)Applicant : TOKAI CARBON CO LTD  
TOKYO ELECTRON LTD

(22)Date of filing : 28.04.1998

(72)Inventor : HAINO KAZUYOSHI  
KAZAMA KOICHI

## (54) PROTECTING MEMBER FOR INNER WALL OF CHAMBER AND PLASMA PROCESSOR

### (57)Abstract:

**PROBLEM TO BE SOLVED:** To provide a protecting member for the inner wall of the chamber of a plasma processor, which can be used for a long time by specifying the material property of glass-like carbon material and the plasma processor, wherein the described protecting member is arranged.

**SOLUTION:** A chamber inner-wall protecting member 2 is a hollow-shaped protecting member, which protects the inner wall of the chamber of a plasma processor, and is formed of the glass-like carbon material having the characteristics of the volume resistivity of  $1 \times 10^{-2} \Omega \cdot \text{cm}$  or less and a thermal conductivity of 5 W/m.K or more as an integral body structure. It is preferable that the thickness of the protecting member 2 be 4 mm or more, and the average roughness (Ra) of the inside surface of 2.0  $\mu\text{m}$  or less. The plasma processor is so constituted that the chamber inner-wall protecting member 2 having these material properties is arranged along the chamber inner-wall part of the plasma processor, the chamber inner-wall part and the protecting member 2 are conducted electrically, and the chamber is grounded.

